



NOTE :
 SHAFT OPTION S1: SMOOTH OUTPUT SHAFT(STANDARD)
 SHAFT OPTION S2: OUTPUT SHAFT WITH KEYWAY

CM No.#	Conjunction Plate	Applicability By Ratio										Dimension [Unit : mm]												
		25	30	35	40	45	50	60	70	80	90	100	C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	X1
CM1	11L30□											63	4-M4x8	11 std 12 max	26.5	40	3.5	55	29.5	99.5	8.75	69.5	5	74
	11S30□	○																						
	17L30□																							
	17S30□																							
	23L20□																							
23S30□	-										66.675	4-M4x8	11 std 12 max	33.5	38.15	3.5	60	36.5	106.5	15.75	76.5	12		
56B10□																								
56B20□																								
60A10□																								
60A20□																								
60A40□											70	4-M5x10	11 std 12 max	31.5	50	6.5	60	34.5	104.5	13.75	74.5	10	78	

Date	2012.05.07 (2008.04.15/2011.05.17)	Title	Cool Muscle Gear 2-stage CM-ABR060
Scale	1 : 1	Dwg No.	CMABR0602-30
Size	A2		
3RD Angle Projection			